

ELECTRIC FORKLIFT TRUCK SERIES R 120-160

CAPACITY 12.000-16.000 Kg
CENTER OF GRAVITY 600mm
VOLTAGE 120V
HYDRAULIC
TILTABLE CAB FOR A
QUICK AND EASY
BATTERY CHANGE,
HIGH PERFORMANCES,
LONG AUTONOMY AND
COMPACT SIZE.

R

carer
Electric Forklift Trucks




carer
Electric Forklift Trucks

C.A.R.E.R. Srl
Via Copernico 13
48010 Cotignola (RA) Italia
Tel. +39 0545 1938010
Fax +39 0545 908070
info@carerforklift.com
www.carerforklift.com

MAIN FEATURES

- LOAD CAPACITY 12.000-16.000 Kg
- CENTER OF GRAVITY 600mm
- VOLTAGE 120V
- COMPLETE TILTABLE CABIN
- TYRES DUAL SUPER ELASTIC
- DC MOTORS
- MULTIFUNCTION EASY INFO (MDE)
- OIL IMMERSSED BRAKES
- TRAVEL SPEED 10, km/h
- LIFTING SPEED 0,26 m/s
- BATTERY 120V 1550Ah
- LOW POSITIONED TILT CYLINDERS



a=200

The benefits of choosing CARER

This truck is the ultimate expression of the strength and power of the standard range of Carer forklifts, coming to handle loads up to 16,000 kg. Equipped with tilting cabins for quick and easy battery change, this truck manages to combine high performance, long working cycles and compact in size.

Specifications

The superelastic tires make this family of trucks ideal for outdoor use.

The driver's space is carefully designed to provide maximum operator comfort: The steering wheel and seat are equipped with a wide range of adjustments and visibility is perfect in every direction.

The electronic control of traction

and lifting guarantees silent operation and maximum performance.

Technical features

The series trucks R120-160 are equipped with a sturdy axle which allows sharp steering angles. The brakes in oil bath ensure maximum effectiveness of the braking and reduce maintenance costs. The electric braking energy recovery can be adjusted in intensity according to the preferences of the operator.

The hydraulic cilinder tilts the cab, to be able to change the two batteries that are placed between the two axles of the machine. The batteries can be changed using the forkpockets underneath the battery containers.



		CARER			
		R120	R160		
CHARACTERISTICS	1,1	Manufacturer			
	1,2	Type			
	1,3	Power Source: Battery, diesel, gas, electric mains	battery	battery	
	1,4	Operation: manual, pedestrian, stand, seat	seat	seat	
WEIGHTS	1,5	Load capacity	Q (t)	12,0	16,0
	1,6	Load center	C (mm)	600	600
	1,8	Load distance	X (mm)	860 (1)	950 (1)
TYRES	1,9	Wheelbase	Y (mm)	2915	3020
	2,1	Unladen weight (max. battery)	(kg)	20025	26500
	2,2	Axle loading laden front/rear (max. battery)	(kg)	29460/2565	39900/2600
	2,3	Axle loading unladen front/rear (max. battery)	(kg)	11450/8575	15690/10810
	3,1	Tyres: C= cushion, SE= super-elastic, PN= Pneumatic, SEG= dual super-elastic PNG= dual pneumatic, VLK= vulkollan		SEG	SEG
	3,2	Tyre size, front		12.00-20	12.00-20
DIMENSIONS	3,3	Tyre size, rear		12.00-20	12.00-20
	3,5	Wheels: Number front / rear (X = driven)		4X/2	4X/2
	3,6	Track width, front, standard/wide tread	b10 (mm)	1835	1835
	3,7	Track width, rear	b11 (mm)	1786	1786
	4,1	Mast tilt, forward α / back β	α/β (°)	7/10 (2)	7/10 (2)
	4,2	Height of mast lowered	h1 (mm)	2900	3250
	4,3	Free lift	h2 (mm)	0	0
	4,4	Lift height	h3 (mm)	3400	3600
	4,5	Height of mast extended	h4 (mm)	4990	5120
	4,7	Height to top of overhead guard	h6 (mm)	2830	2830
	4,8	Seat height	h7 (mm)	1750	1750
	4,12	Towing coupling height	h10 (mm)	1200	1200
	4,19	Overall length	L1 (mm)	5645	5850
	4,20	Length to face of fork	L2 (mm)	4445	4650
	PERFORMANCES	4,21	Overall width, standard / wide tread	b1 (mm)	2485
4,22		Fork dimensions	exsXL (mm)	200x80x1200	220x90x1200
4,23		Fork carriage ISO 2328/30, FEM / A, B		CARER	CARER
4,24		Fork carriage width	b3 (mm)	2200	2200
4,31		Ground clearance under mast, laden	m1 (mm)	180	180
4,32		Ground clearance at center of wheelbase	m2 (mm)	300	300
4,33		Aisle width with pallets 1000x1200mm wide	Ast (mm)	6490	6750
4,34		Aisle width with pallets 800x1200mm long	Ast (mm)	6690	6950
4,35		Outer turning radius	Wa (mm)	4430	4600
4,36		Inner turning radius, standard/wide tread	b13 (mm)	2000	2130
MOTORS / BATT.	5,1	Travel speed, with / without load	(km/h)	9,0/10,0	7,5/9,0
	5,2	Lifting speed, with / without load	(m/s)	0,17/0,26	0,15/0,24
	5,3	Lowering speed with / without load	(m/s)	0,40/0,40	0,40/0,40
	5,5	Drawbar pull, with / without load (S2 60 °)	(N)	13900/15600	12900/15000
	5,6	Max drawbar pull, with / without load (S2 5 °)	(N)	34000/35700	33000/35200
	5,7	Gradeability, with / without load (S2 30 °)	(%)	8,8/15,1	6,9/12,2
	5,8	Max gradeability, with / without load (S2 5 °)	(%)	10,8/18,4	8,5/14,9
	5,9	Acceleration time, with / without load (10 m)	(s)	6,5/5,2	7,4/6
	5,10	Service brake: mech. / Hydraulic / electric		hydr/elect	hydr/elect
OTHER	6,1	Drive motor output (S2 60 °)	(kW)	50	50
	6,2	Lifting motor (S3 20%)	(kW)	42	42
	6,4	Battery voltage	U (V)	120	120
	6,4.1	Battery capacity	K5 (Ah)	1250/1400/1550	1400/1550
	6,5	Battery weight minimum / maximum	(kg)	4450/5700	5300/5700
	8,1	Drive control		mosfet	mosfet
	8,2	Working pressure for attachments	(bar)	160	160
	8,4	Average noise level at operator's ear	(dBA)	-	-

VDI 2198

(1) With integral side-shift on the mast

(2) Lifting heights > 4.5 m, 3°/7°.

The performance data refer to forklift truck in perfect efficiency, with battery weight corresponding to the values given in 6,5